
Bootstrap Autocomplete Documentation

Release 2.3.7

Paolo Casciello, Luca Zarotti, see contributors

Jan 18, 2022

Contents

1	Features	3
2	Getting Started	5
3	Basic usage	7
3.1	Text Autocomplete	7
3.2	Response Format	8
3.3	Select Autocomplete	8
3.4	Response Format for Select	8
3.5	Events	8
4	Reference	11
4.1	Activating Autocomplete	11
4.2	Configuration options	11
5	Advanced usage	15
5.1	Set custom resolver	15
5.2	Set custom value	15
5.3	Clear value	16
5.4	Show autocomplete	16
5.5	Customize results using default AJAX resolver	16
6	Demo and Examples	17
7	Translating messages	19
8	Issues, Support and New Features requests	21
9	Development Environment	23
	Index	25

Version: 2.3.7

- **Fast.**
- **Easy.** No complex configuration. HTML attributes supported.
- **Modals supported.** No problems in modals.
- **Customizable.** You can customize every single step in the suggesting workflow.
- **Batteries included.** It works out of the box for Bootstrap v3 and v4.
- **i18n.** Use `data-*` attributes to specify the strings to use in case of errors/noresults.
- **Styles.** No custom styles. Uses standard Bootstrap's dropdown.

CHAPTER 2

Getting Started

Bootstrap Autocomplete works as a plugin. Add it to your page

```
<script src="bootstrap-autocomplete.min.js"></script>
```

Using CDN (thanks to JSDelivr)

Listing 1: STABLE version 2.3.7

```
<script src="https://cdn.jsdelivr.net/gh/xcash/bootstrap-autocomplete@v2.3.7/dist/  
↳latest/bootstrap-autocomplete.min.js"></script>
```

Listing 2: Latest version (this is the development branch)

```
<script src="https://cdn.jsdelivr.net/gh/xcash/bootstrap-autocomplete@master/dist/  
↳latest/bootstrap-autocomplete.min.js"></script>
```

Using NPM

```
npm install bootstrap-autocomplete
```

Using YARN

```
yarn add bootstrap-autocomplete
```

That's it! Go on to enhance your text fields! :)

3.1 Text Autocomplete

Autocomplete is not enabled by default. You must activate it on the fields you want to enhance. Of course you can also use a wide selector to enable it on specific classes or tags.

Suppose you have a field as follows

```
<input class="form-control basicAutoComplete" type="text" autocomplete="off">
```

Here the class `basicAutoComplete` is used to identify all the fields on which to activate a basic autocomplete. Then in Javascript we activate it:

```
$('.basicAutoComplete').autocomplete({
  resolverSettings: {
    url: 'testdata/test-list.json'
  }
});
```

In this example we specified the `url` to use. Autocomplete will automatically make an Ajax GET request to that URL using an argument named `q` with the text typed by the user. Rate limits are enforced and minimum field length is 2.

Even simpler you can pass the URL directly in the markup

```
<input class="form-control basicAutoComplete" type="text"
  data-url="myurl"
  autocomplete="off">
```

and enhance it just with

```
$('.basicAutoComplete').autocomplete();
```

3.2 Response Format

We know how to start an autocomplete lookup but what about the results?

The *default* configuration expects a simple list in JSON format. Like

```
[
  "Google Cloud Platform",
  "Amazon AWS",
  "Docker",
  "Digital Ocean"
]
```

3.3 Select Autocomplete

One of the main features of Bootstrap Autocomplete is to enhance `<select>` fields as easy as `<input>` text fields. Selects are useful to **restrict choices** to a set of possibilities.

Enhancing a select is no different than text fields.

```
<select class="form-control basicAutoSelect" name="simple_select"
  placeholder="type to search..."
  data-url="testdata/test-select-simple.json" autocomplete="off"></select>
```

```
$('.basicAutoSelect').autocomplete();
```

Nice! :)

3.4 Response Format for Select

In this case we need two values in the response: an `id` and a `text`.

```
[
  { "value": 1, "text": "Google Cloud Platform" },
  { "value": 2, "text": "Amazon AWS" },
  { "value": 3, "text": "Docker" },
  { "value": 4, "text": "Digital Ocean" }
]
```

3.5 Events

Bootstrap Autocomplete triggers usual events.

`change` - Value changed

And custom.

`autocomplete.select` - (evt, item) The element `item` is the item selected by the user and currently selected in the field or *null/undefined* if cleared.

`autocomplete.freevalue` - (evt, value) The text field contains *value* as the custom value (i.e. not selected from the choices dropdown).

`autocomplete.dd.shown` - (evt) **V4 only**. Fired when the autocomplete dropdown is shown.

`autocomplete.dd.hidden` - (evt) **V4 only**. Fired when the autocomplete dropdown is hidden.

4.1 Activating Autocomplete

`$ (...).autocomplete([options])`

Enhance the form fields identified by the selector

Arguments

- **options** – Configuration options of type `ConfigOptions`.

4.2 Configuration options

formatResult

callback (*item*)

Arguments

- **item** (*object*) – The item selected or rendered in the dropdown.

Returns An object `{ id: myItemId, text: myfancyText, html?: myfancierHtml }`.

minLength

Default: 3. Minimum character length to start lookup.

autoSelect

Default: `true`. Automatically selects selected item on *blur event* (i.e. using TAB to switch to next field).

resolver

Default: `ajax`. Resolver type. `custom` to implement your resolver using *events*.

noResultsText

Default: `No results`. Text to show when no results found. Use `' '` to disable.

bootstrapVersion

Default: `auto`. Specify Bootstrap Version. Default is `autodetect`. Values: `auto`, `4`, `3`

preventEnter

Default: `false`. Prevent default Enter behavior. Setting this to `true` is useful to prevent form submit.

resolverSettings

Object to specify parameters used by default resolver.

url

Url used by default resolver to perform lookup query.

queryKey

Default: `q` Default query key.

requestThrottling

Default: `500`. Time to wait in ms before starting a remote request.

fail

Default: `undefined`. Callback in case of AJAX error.

events

Object to specify custom event callbacks.

search

func (*qry, callback, origJQElement*)

Function called to perform a lookup.

Arguments

- **qry** (*string*) – Query string.
- **callback** – Callback function to process results. Called passing the **list** of results `callback(results)`.
- **origJQElement** (*JQuery*) – Original jQuery element.

searchPost

func (*resultsFromServer, origJQElement*)

Function called to manipulate server response. Bootstrap Autocomplete needs a list of items. Use this function to convert any server response in a list of items without reimplementing the default AJAX server lookup.

Arguments

- **resultsFromServer** – Result received from server. Using the default resolver this is an object.
- **origJQElement** (*JQuery*) – Original jQuery element.

Returns List of items.

Following events are available to fine tune every lookup aspect. Rarely used in common scenarios

typed

func (*newValue, origJQElement*)

Field value changed. Use this function to change the searched value (like prefixing it with some string, filter some characters, ...). Or to stop lookup for certain values.

Arguments

- **newValue** (*string*) – New value.
- **origJQElement** (*JQuery*) – Original jQuery element.

Returns (Un)modified value or `false` to stop the execution.

searchPre**func** (*newValue*, *origJQElement*)

Before starting the search. Like in the `typed` event, this function can change the search value. The difference is this event is called *after* `minLength` checks.

Arguments

- **newValue** (*string*) – New value.
- **origJQElement** (*JQuery*) – Original jQuery element.

Returns (Un)modified value or `false` to stop the execution.

As a reference the lookup workflow calls events in the following order:

```
typed -> searchPre -> search -> searchPost
```


5.1 Set custom resolver

Default resolver often is not enough. You can customize it as follows.

```
$('.advancedAutoComplete').autocomplete({
  resolver: 'custom',
  events: {
    search: function (qry, callback) {
      // let's do a custom ajax call
      $.ajax(
        '<url>',
        {
          data: { 'qry': qry }
        }
      ).done(function (res) {
        callback(res.results)
      });
    }
  }
});
```

Request throttling is not working with custom resolvers. You should implement your logic.

5.2 Set custom value

To set an initial or change the value of the field.

```
$('.myAutoSelect').autocomplete('set', { value: myValue, text: myText });
```

5.3 Clear value

To clear the value.

```
$('.myAutoSelect').autocomplete('set', null);  
// or  
$('.myAutoSelect').autocomplete('clear');
```

5.4 Show autocomplete

Sometimes is useful to programmatically show suggestions. To achieve this set a `minLength` of 0, server side acts accordingly with a `qry` value of `' '`, call the following method:

```
$('.myAutoSelect').autocomplete('show');
```

5.5 Customize results using default AJAX resolver

Using the `searchPost` event you can manipulate the result set making it compatible with autocomplete default. This is useful to bypass the customization of the entire search AJAX call.

```
$('.myAutoSelect').autocomplete({  
  events: {  
    searchPost: function (resultFromServer) {  
      return resultFromServer.results;  
    }  
  }  
});
```

CHAPTER 6

Demo and Examples

You can view Demo and Examples [here](#).

Translating messages

To customize “no results” message use the following markup.

```
<select class="form-control emptyAutoSelect" name="empty_select"  
  data-url="testdata/test-empty.json"  
  data-noresults-text="Nothing to see here."  
  autocomplete="off"></select>
```


CHAPTER 8

Issues, Support and New Features requests

Feel free to post a [new issue](#)

Development Environment

To setup an environment to develop Bootstrap-Autocomplete you need only Docker and Docker Compose.

The source is in the TypeScript language in the `src` directory while the documentation is generated using Sphinx and resides in the `docs` directory.

Create the development containers:

```
docker-compose build --pull
```

Install dependencies (first time and to update):

```
docker-compose run --rm tools yarn install
```

To start the environment:

```
$ docker-compose up
```

Two servers starts up:

- [Demo page](#)
- [Documentation](#)

Symbols

\$ () (*built-in function*), 11

A

autoSelect (*None attribute*), 11

B

bootstrapVersion (*None attribute*), 11

C

callback () (*built-in function*), 11

E

events (*None attribute*), 12

F

fail (*None attribute*), 12

formatResult (*None attribute*), 11

func () (*built-in function*), 12, 13

M

minLength (*None attribute*), 11

N

noResultsText (*None attribute*), 11

P

preventEnter (*None attribute*), 12

Q

queryKey (*None attribute*), 12

R

requestThrottling (*None attribute*), 12

resolver (*None attribute*), 11

resolverSettings (*None attribute*), 12

S

search (*None attribute*), 12

searchPost (*None attribute*), 12

searchPre (*None attribute*), 12

T

typed (*None attribute*), 12

U

url (*None attribute*), 12